Styletto AX Charger
Styletto IX Charger

Data Sheet



Styletto AX / IX Charger | Technical Data

Type

Device property	
Dimensions (LxWxH)	70.8 x 49.9 x 29.5 mm
Weight without cable	50 g
Ingress Protection Rating	IP XO (ordinary)
Protection against electric shock	class III
Electrical property – Charger	
Power supply connector	USB-C
Input voltage	5 V DC
Input current	≤ 0.5 A
Electrical property – Power supply adapter	
Input voltage	100 – 240 V AC
Input current	0.15 – 0.3 A
Input frequency	50 – 60 Hz
Output voltage	5 V DC
Output current	1 A
Built-in battery	
Battery type	Lithium-ion
Battery capacity (see label on device)	400 mAh / 450 mAh
Battery runtime	4 days in typical use
Charging time (USB)	~ 3 h
Charging time (wireless)	~ 6 h
Operating conditions	
Temperature (USB charging)	+10 … +35 °C / +50 … +95 °F
Temperature (wireless charging)	+10 … +30 °C / +50 … +86 °F
Relative humidity	20 … 75 %
Minimum air pressure	700 hPa
Storage conditions	
Temperature (recommended)	+10 … +25 °C / +50 … +77 °F
Temperature (max.)	+10 … +40 °C / +50 … +104 °F
Relative humidity (recommended)	20 … 80 %
Relative humidity (max.)	10 … 80 %
Transportation conditions	
Temperature	– 20 … +60 °C / – 4 … +140 °F
Relative humidity	5 … 90 %

Note: Due to the design of the Styletto AX / IX, not all earwear couplings will fit inside the Styletto AX / IX Charger.
Recommended couplings: S, M and P-Receivers (length 0 – 3) with Earware 3.0 open and tulip (all sizes) or sleeves (size XS – M).

Styletto AX / IX Charger | Conformance information

		Safety	EN 62368-1:2020
EU	CE	EMC	EN 60601-1-2:2015 + A1:2021
USA	FCC		47 CFR Part 15
Canada	IC		ICES-003 Issue 7 / 2020
Korea	KCC		KN 32 / KN 35

Order No. 04742-99T04-7600
www.wsaud.com
© 02.2024, WSAUD A/S
All rights reserved

Subject to change
without prior notice

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.